



SECURTAPE

SPLICING TAPE

DESCRIPTION

Carlisle's Sure Seal SecurTAPE is an EPDM synthetic rubber-based product which is used for splicing PRE-KLEENED EPDM Thru-Wall Flashing and root barrier and the temporary securing of CCW MiraDRAIN and protection courses. SecurTAPE features a clear poly release film and excellent long-term holding properties.

PROPERTIES AND CHARACTERISTICS:

Name:	SecurTAPE
Size:	3" (76.2mm)
Color:	Black
Base:	Synthetic Rubber EPDM
Cure State:	Cured
Roll Size:	3" X 100' (30.4 in) Long
Thickness:	.030" (0.76 mm) Thick
Packaging:	4 Rolls Per Carton
Net Wt. Per Carton:	26 Pounds (12 Kg)
Shelf Life:	6 Months

CAUTIONS AND WARNINGS

- Review the applicable Material Safety Data Sheet for complete safety information prior to use.
- Avoid prolonged contact with skin. In case of contact with skin, thoroughly wash affected area with soap and water.
- Job site storage temperatures in excess of 90° F (32° C) may affect product shelf life. Prolonged job site exposure to temperatures below 40° F (4° C) will cause the tape to lose tack and in extreme cases not bond to the substrate. If this situation is encountered, remove tape to warm area and allow it to return to a minimum 60° F (15° C). Do not apply heat directly to tape.

- Sure Seal SecurTAPE must be stored in a dry area. Exposure to moisture can damage the protective release paper, making it difficult to remove.
- Under some weather conditions, condensation can form on the EPDM membrane following the cleaning step. The bond strength of Sure Seal SecurTAPE will be negatively effected under these conditions. When these conditions are encountered the Sure-Seal SecurTAPE should be applied to the primed membrane as soon after priming as possible to minimize condensation formation. A heat gun can be used to dry the surface prior to applying the SecurTAPE. If condensation continues, discontinue the use of Sure Seal SecurTAPE.

LIMITED WARRANTY

CARLISLE COATINGS AND WATERPROOFING INCORPORATED (CARLISLE) warrants this product to be free of defects in workmanship and materials only at the time of shipment from our factory. If any CARLISLE materials prove to contain manufacturing defects that substantially affect their performance, CARLISLE will, at its option, replace the material or refund the purchase price.

This limited warranty is the only warranty extended by CARLISLE with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. CARLISLE specifically disclaims liability for any incidental, consequential, or other damages, including but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever.

The dollar value of CARLISLE's liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the CARLISLE material in question.